# **Material Safety Data Sheet**

Sport Kote

# 1. Product and company identification

Product nameSport KoteIn case of emergency1-800-843-6174Code222SFValidation date6/11/2012.Material usesGym FinishPrint date6/11/2012.

Manufacturer Essential Industries, Inc. Responsible name Regulatory Affairs Department

P.O. Box 12 Merton, WI 53056-0012 Phone: 262-538-1122

### Hazardous Material Information System (U.S.A.)

| Health              | * 1 HAZARD<br>RATING         |
|---------------------|------------------------------|
| Flammability        | 0 4 = Extreme<br>3 = High    |
| Physical hazards    | 0 2 = Moderate<br>1 = Slight |
| Personal protection | B 0 = Insignificant          |

A = Goggles B = Goggles & Gloves C = Goggles, Gloves & Apron

### 2. Hazards identification

Emergency overview CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. May be

harmful if inhaled or swallowed. May cause eye and skin irritation.

Do not breathe vapor or mist. Do not ingest. Do not get in eyes. Avoid contact with skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

#### Potential acute health effects due to overexposure

Inhalation May be harmful by inhalation.
Ingestion May be harmful if swallowed.

Skin May cause skin irritation. May be absorbed through skin with prolonged or repeated contact.

Eyes May cause eye irritation.

Potential chronic health effects due to overexposure

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

See toxicological information (section 8)

## 3. Composition/information on ingredients

 Name
 CAS number
 %

 2-(2-butoxyethoxy)ethanol
 112-34-5
 1 - 5

 N-methyl-2-pyrrolidone
 872-50-4
 1 - 5

 2-butoxyethanol
 111-76-2
 1 - 5

SARA 313 (Form R - Reporting requirements)

 Product name
 CAS number
 Concentration

 2-(2-butoxyethoxy)ethanol
 112-34-5
 3.9

 N-methyl-2-pyrrolidone
 872-50-4
 1.3

 2-butoxyethanol
 111-76-2
 1.3

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient nameCancerReproductiveNo significant risk levelMax acceptable dosageN-methyl-2-pyrrolidoneNo.Yes.No.3200 µg/day (inhalation)

### 4. First aid measures

Eye contact Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes,

occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get

medical attention if irritation develops.

Inhalation Move exposed person to fresh air. Get medical attention if symptoms appear. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical

attention immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. Get medical attention immediately.

### First aid measures

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

Notes to physician

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled

#### 5. Fire-fighting measures

Flammability of the product

In a fire or if heated, a pressure increase will occur and the container may burst.

**Extinguishing media** 

Suitable

Use an extinguishing agent suitable for the surrounding fire.

Special exposure hazards Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action

shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition Decomposition products may include the following materials:

products

carbon dioxide carbon monoxide nitrogen oxides

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA)

with a full face-piece operated in positive pressure mode.

Flash point Closed cup: >93.30°C (>200°F)

#### Control and preventive measures 6.

**Storage** 

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

| Ingredient             | Exposure limits   |
|------------------------|---|
| N-methyl-2-pyrrolidone | AIHA WEEL (United States, 5/2010). Absorbed through skin. |
|                        | TWA: 10 ppm 8 hour(s).                                    |
| 2-butoxyethanol        | OSHA PEL (United States, 6/2010). Absorbed through skin.  |
|                        | TWA: 50 ppm 8 hour(s).                                    |
|                        |   |

### **Personal protection**

Respiratory

None required with adequate ventilation. In situations where respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the

appropriate regulatory standards and/or industrial recommendations.

Hands

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when

handling chemical products if a risk assessment indicates this is necessary.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is

necessary to avoid exposure to liquid splashes, mists or dusts.

Methods for cleaning up

**Small spill** 

Skin

**Eyes** 

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Waste disposal

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Physical and chemical properties

Liquid **Boiling/condensation point** 100°C (212°F) **Physical state** Melting/freezing point Color Yellow [Light] 0°C (32°F) Bland [Slight] Vapor pressure <4 kPa (<30 mm Hg) Odor

<1 [Air = 1] 7.5 - 8.5Vapor density pН Not applicable Weight per Gallon: 8.70 lbs/gal 1% pH: **Specific Gravity:** 1.04 gm/ml VOC \* 254 gm/L

<sup>\*</sup> Meets CARB Suggested Control Measure (SCM) for Architectural Coatings and South Coast Air Quality Management Board (SCAQMD) rules.

#### **Toxicological information** 8.

Acute toxicity
Product/ingredient name
2-butoxyethanol **Dose** 250 mg/kg 2900 mg/m3 Result LD50 Oral Species Rat **Exposure** LC50 Inhalation Vapor 7 hours LC50 Inhalation Gas. Rat 450 ppm 4 hours

2-(2-butoxyethoxy)ethanol LD50 Oral Rat 5660 mg/kg N-methyl-2-pyrrolidone LD50 Oral Rat 3914 mg/kg

**Conclusion/Summary** Not available

**Chronic toxicity** 

Conclusion/Summary Not available

#### 9. **Transport information Regulatory information** PG\* **UN** number **Proper shipping name** Classes Label **Additional information DOT Classification** Not regulated

PG\*: Packing group