



Fisher Scientific

Part of Thermo Fisher Scientific

Material Safety Data Sheet

Creation Date 28-Apr-2009

Revision Date 11-Mar-2014

Revision Number 5

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	Acetone
Cat No. :	A9-4; A9-20; A9-200; A11-1; A11-4; A11-20; A11-200; A11S-4; A16F-1GAL; A16P-1GAL; A16P-4; A16S-4; A16S-20; A18-1; A18-4; A18-20; A18-200; A18-200LC; A18-500; A18CU1300; A18FB-19; A18FB-50; A18FB-115; A18FB-200; A18P-4; A18POP-19; A18POPB-50; A18RB-19; A18RB-50; A18RB-115; A18RB-200; A18RS-28; A18RS-50; A18RS-115; A18RS-200; A18S-4; A18SK-4; A18SS-19; A18SS-28; A18SS-50; A18SS-115; A18SS-200; A19-1; A19-4; A19RS-115; A19RS-200; A40-4; A928-4; A929-1; A929-4; A929RS-19; A929RS-50; A929RS-200; A929SK-4; A929SS-28; A929SS-50; A929SS-115; A929SS-200; A946-4; A946-4LC; A946FB-200; A946RB-19; A946RB-50; A946RB-115; A946RB-200; A949-1; A949-4; A949CU-50; A949N-119; A949N-219; A949POP-19; A949RS-28; A949RS-50; A949RS-115; A949SK-1; A949SK-4; A949SS-19; A949SS-28; A949SS-50; A949SS-115; A949SS-200; BP2403-1; BP2403-4; BP2403-20; BP2404-1; BP2404-4; BP2404SK-1; BP2404SK-4; HC-300-1GAL; 22050131; 22050295
Synonyms	2-Propanone; Dimethyl ketone; (Certified ACS, HPLC, OPTIMA, Histological, Spectranalyzed, NF/FCC/EP, Pesticide, Electronic, GC Resolv, SAFE-COTE)
Recommended Use	Laboratory chemicals
Company	Emergency Telephone Number
Fisher Scientific	CHEMTREC®, Inside the USA: 800-424-9300
One Reagent Lane	CHEMTREC®, Outside the USA: 001-703-527-3887
Fair Lawn, NJ 07410	
Tel: (201) 796-7100	

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Flammable liquid and vapor. Irritating to eyes and skin. May cause irritation of respiratory tract. Vapors may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

Appearance Colorless

Physical State Liquid

Odor sweet

Target Organs

Central nervous system (CNS), Liver, Kidney, Blood, Bone Marrow, Skin

Potential Health Effects**Acute Effects****Principle Routes of Exposure**

Eyes	Irritating to eyes.
Skin	Irritating to skin. May be harmful in contact with skin. Repeated exposure may cause skin dryness or cracking.
Inhalation	May be harmful if inhaled. Inhalation may cause central nervous system effects. May cause drowsiness and dizziness. May cause irritation of respiratory tract.
Ingestion	May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects

Experiments have shown reproductive toxicity effects on laboratory animals. May cause adverse liver effects. May cause adverse kidney effects.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions

Central nervous system disorders. Preexisting eye disorders. Skin disorders. Kidney disorders. Liver disorders.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Haz/Non-haz

Component	CAS-No	Weight %
Acetone	67-64-1	>95

4. FIRST AID MEASURES

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.
Ingestion	Do not induce vomiting. Obtain medical attention.
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point	-20°C / -4°F
Method -	Closed cup
Autoignition Temperature	465°C / 869°F
Explosion Limits	
Upper	12.8 vol %
Lower	2.5 vol %
Oxidizing Properties	Not oxidising
Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water spray. Cool closed containers exposed to fire with water spray.
Unsuitable Extinguishing Media	Water may be ineffective

Hazardous Combustion Products	No information available.
Sensitivity to mechanical impact	No information available.
Sensitivity to static discharge	No information available.

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA	Health 1	Flammability 3	Instability 0	Physical hazards N/A
-------------	-----------------	-----------------------	----------------------	-----------------------------

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Keep people away from and upwind of spill/leak. Avoid contact with skin, eyes and inhalation of vapors..
Environmental Precautions	Should not be released into the environment.
Methods for Containment and Clean Up	Remove all sources of ignition. Take precautionary measures against static discharges. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. HANDLING AND STORAGE

Handling	Wear personal protective equipment. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. Use explosion-proof equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Storage	Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	TWA: 500 ppm STEL: 750 ppm	(Vacated) TWA: 750 ppm (Vacated) TWA: 1800 mg/m ³ (Vacated) STEL: 2400 mg/m ³ (Vacated) STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m ³	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Acetone	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³ STEL: 1260 ppm STEL: 3000 mg/m ³	TWA: 500 ppm STEL: 750 ppm

Legend

NIOSH IDLH: Immediately Dangerous to Life or Health

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Colorless
Odor	sweet
Odor Threshold	19.8 ppm
pH	7
Vapor Pressure	247 mbar @ 20 °C
Vapor Density	2.0
Viscosity	0.32 mPa.s @ 20 °C
Boiling Point/Range	56°C / 132.8°F
Melting Point/Range	-95°C / -139°F
Decomposition temperature	> 4°C
Flash Point	-20°C / -4°F
Method -	Closed cup
Evaporation Rate	5.6 (Butyl Acetate = 1.0)
Specific Gravity	0.790
Solubility	Soluble in water
log Pow	No data available
Molecular Weight	58.08
Molecular Formula	C ₃ H ₆ O

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to Avoid	Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated compounds, Alkali metals, Amines
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Formaldehyde, Methanol
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit) > 7400 mg/kg (rat)	76 mg/l, 4 h, (rat)

Irritation	Irritating to eyes and skin
Toxicologically Synergistic Products	Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane; Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene; Acetonitrile, 2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene
Chronic Toxicity	
Carcinogenicity	There are no known carcinogenic chemicals in this product
Sensitization	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
Other Adverse Effects	Neurotoxic effects have occurred in experimental animals..
Endocrine Disruptor Information	No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96 h)	Oncorhynchus mykiss: LC50 = 5540 mg/l 96h Alburnus alburnus: LC50 = 11000 mg/l 96h Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h

Persistence and Degradability Readily biodegradable. .

Bioaccumulation/ Accumulation No information available

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Acetone	-0.24

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

14. TRANSPORT INFORMATION

DOT

UN-No UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II

TDG

UN-No UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II

IATA

UN-No UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II

IMDG/IMO

UN-No UN1090
Proper Shipping Name ACETONE
Hazard Class 3
Packing Group II

14. TRANSPORT INFORMATION

15. REGULATORY INFORMATION

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	CHINA	KECL
Acetone	X	X	-	200-662-2	-		X	X	X	X	X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Not applicable

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Not applicable

Clean Air Act

Not applicable

OSHA Occupational Safety and Health Administration

OSHA - Occupational Safety and Health Administration

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Acetone	2000 lb STQ

Other International Regulations


Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid
 D2B Toxic materials



16. OTHER INFORMATION

Prepared By Regulatory Affairs
 Thermo Fisher Scientific
 Email: EMSDS.RA@thermofisher.com

Creation Date 28-Apr-2009

Print Date 11-Mar-2014

Revision Summary Update to Format, (M)SDS sections updated, 4, 8, 9, 11, 12, 15, 16.

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS