

Material Safety Data Sheet

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:SCOTCH BRAND Permanent White Glue Stick 6008, 6015, 6020, 6036, 6040, 003, 0038**MANUFACTURER:**3M**DIVISION:**Stationery Products

ADDRESS: 3M Center St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 05/12/09 **Supercedes Date:** 12/19/08

Document Group: 09-4549-3

Product Use:

Intended Use:

Adhesive

SECTION 2: INGREDIENTS

Ingredient	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	60 - 65
N-VINYLPYRROLIDINONE POLYMER	9003-39-8	14 - 16
SUCROSE	57-50-1	7 - 9
POLYETHYLENE GLYCOL	25322-68-3	6 - 8
SODIUM STEARATE	822-16-2	5 - 7
SODIUM HYDROXIDE	1310-73-2	0.4 - 0.6

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste **Odor, Color, Grade:** White with fatty acid/acrylic odor. **General Physical Form:** Solid **Immediate health, physical, and environmental hazards:**

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

No health effects are expected.

Ingestion:

No health effects are expected.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: No need for first aid is anticipated.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL OSHA Flammability Classification: Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable

5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

MATERIAL SAFETY DATA SHEET SCOTCH BRAND Permanent White Glue Stick 6008, 6015, 6020, 6036, 6040, 003, 0038 05/12/09

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Ventilate the area with fresh air. Collect as much of the spilled material as possible. Clean up residue with detergent and water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact.

7.2 STORAGE

Store under normal warehouse conditions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection Avoid eye contact.

8.2.2 Skin Protection

Not applicable.

8.2.3 Respiratory Protection

Not applicable.

8.2.4 Prevention of Swallowing

Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	Type	<u>Limit</u>	Additional Information
N-VINYLPYRROLIDINONE POLYMER	CMRG	TWA, as respirable	5 mg/m3	
		dust		
N-VINYLPYRROLIDINONE POLYMER	CMRG	TWA, as total dust	10 mg/m3	

POLYETHYLENE GLYCOLS SODIUM HYDROXIDE SODIUM HYDROXIDE SODIUM HYDROXIDE SODIUM HYDROXIDE STEARATES SUCROSE SUCROSE	AIHA ACGIH CMRG OSHA OSHA ACGIH ACGIH OSHA	TWA, as aerosol CEIL TWA CEIL TWA TWA, as total dust TWA TWA, respirable	10 mg/m3 2 mg/m3 2 mg/m3 2 mg/m3 2 mg/m3 10 mg/m3 10 mg/m3 5 mg/m3	Table Z-1A Table Z-1 Table A4 Table A4 Table Z-1
SUCROSE SUCROSE	OSHA OSHA	TWA, respirable TWA, as total dust	5 mg/m3 15 mg/m3	Table Z-1 Table Z-1

SOURCE OF EXPOSURE LIMIT DATA: ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Paste **Odor, Color, Grade:** White with fatty acid/acrylic odor. **General Physical Form:** Solid Autoignition temperature Not Applicable **Flash Point** Not Applicable Not Applicable **Flammable Limits - LEL** Not Applicable Flammable Limits - UEL Not Applicable **Boiling point** 0.95 - 1 g/cm3 Density Vapor Density Not Applicable Vapor Density Not Applicable Vapor Pressure Not Applicable Vapor Pressure Not Applicable **Specific Gravity** 0.95 - 1.0 [*Ref Std:* WATER=1] Approximately 10.3 Units not avail. or not appl. pН Melting point Approximately 140 °F Solubility in Water Appreciable Not Applicable **Evaporation rate** Percent volatile 60 - 65 % weight Viscosity Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

41-3700-5412-8, 41-3700-5422-7, 44-0028-8703-0, 44-0040-0578-9, 44-0040-1352-8, 44-0040-1353-6, 44-0040-1354-4, 44-0040-1355-1, 44-0040-5914-1, 44-0040-5915-8, 44-0040-5916-6, 44-0040-5917-4, 44-0040-5918-2, 70-0050-3211-8, 70-0050-3431-2, 70-0709-7778-3, 70-0709-7779-1, 70-0709-7781-7, 70-0709-7821-1, 70-0709-9201-4, 70-0709-9872-2, 70-0710-2681-2, 70-0710-2705-9, 70-0710-2733-1, 70-0710-3228-1, 70-0710-3366-9, 70-0710-3425-3, 70-0710-3459-2, 70-0710-6564-6, 70-0710-8060-3, 70-0710-8946-3, 70-0710-8951-3, 70-0711-5483-8, 70-0711-7720-1, 70-0711-7786-2, 70-0711-7815-9, 70-0711-7816-7, 70-0712-0526-7, 70-0712-0710-7, 70-0712-0711-5, 70-0712-0712-3, 70-0712-0713-1, 70-0712-1480-6, 70-0712-1537-3, 70-0712-1574-6, 70-0712-1590-2, 70-0712-1593-6, 70-0712-1594-4, 70-0712-1599-3, 70-0712-1782-5, 70-0712-1806-2, 70-0713-0376-5, 70-0713-0555-4, 70-0713-0556-2, 70-0713-0658-6, 70-0713-0659-4, 70-0713-0660-2, 70-0713-0661-0, 70-0713-0376-5, 70-0713-0555-4, 70-0713-0556-2, 70-0713-0658-6, 70-0713-0659-4, 70-0713-0779-0, 70-0713-2301-1, 70-0713-0728-7, 70-0713-0775-8, 70-0713-0776-6, 70-0713-0777-4, 70-0713-0778-2, 70-0713-6175-5, 70-0713-6648-1, 70-0713-4977-6, 70-0713-4991-7, 70-0713-5080-8, 70-0713-5180-6, 70-0713-6175-5, 70-0713-6648-1, 70-0713-9201-6, 70-0713-9381-6, 70-0713-9431-9, 70-0713-9508-4, 70-0713-8353-6, 70-0713-9121-6, 70-0713-9128-1, 70-0713-9201-6, 70-0713-9381-6, 70-0713-9431-9, 70-0713-9508-4, 70-0714-826-6, 70-0714-2257-3, 70-0714-2261-5, 70-0714-2291-2, 70-0714-8244-5, 70-0714-9783-1, 70-0715-0364-6

MATERIAL SAFETY DATA SHEET SCOTCH BRAND Permanent White Glue Stick 6008, 6015, 6020, 6036, 6040, 003, 0038 05/12/09

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 0 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes: Copyright was modified. Section 14: ID Number(s) Template 1 was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com